

TC320

Business Analog Portable Radio

Unique for its compact and professional design, as well as its superb sound quality. Its strong casing prevents damage against drops of up to 5ft. This radio enables businesses to enjoy dependable communications at an extremely low cost.





- Wide Communication Range2W output power has a range of up to 6 miles.
- Durable Casing
 Compact durable design that can with stand a 1.5 meter drop.
- Long Battery Life
 1700mAh high capacity Li-lon battery lasts approximately 12hrs.
- User Friendly Design
 With its ergonomic design, this slim and compact radio can
 enhance user comfort, while maintaining a professional and
 fashionable appearance.
- Double Injection Molding
 The combination of double injection molding and grip technology brings users a comfortable and convenient operation experience.
- Mini-USB Interface
 Chargeable and Programmable through the Mini-USB port, plug directly into an outlet or the optional charger.

Features

- Audio Compandor
- Scrambler compatible w/ TC320 UHF2 & TC518
- VOX Earpiece
- Battery Strength Indicator
- High / Low Power Switchable
- Programmable 25 / 12.5 KHz Channel Spacing
- Monitor
- CTCSS / CDCSS and Squelch Tail Elimination
- Channel Scan
- Auto Battery Save
- Low Battery Alert
- Busy Channel Lockout (BCL)
- Time-out-timer (TOT)
- PC Programmable
- Wired Clone

Applications

Retail

Hotel

Restaurants

Education

Hospital

Business

Property Management









Accessories

Included

- Li-lon Battery
- Power Supply
- Antenna
- Belt Clip
- Neck Strap



Earpiece with In-Line MIC, PTT, & VOX EHS09



Rapid-rate Charger (for Li-lon Battery) CH05L01



Programming Cable (USB Port) PC30



6-Unit Switching Power (Combine w/ CH05L01) PS4001

Specifications

See website for full list

General	Frequency Range	UHF1: 400 - 470MHz ; UHF2: 450-470MHz
	Channel Capacity	16
	Channel Spacing	25 / 12.5KHz
	PLL Channel Stepping	5 kHz, 6.25 kHz
	Operating Voltage	3.7V (rated)
	RF Power Output	2W
	Battery	1700mAh (Li-lon)
	Battery Life (5-5-90 Duty Cycle)	Approx. 10hrs
	Frequency Stability	±0.5ppm
	Operating Temperature	-4° F ~ 131° F
	Antenna Impedance	50 Ω
	Dimensions (HxWxD)	3.94 x 1.89 x 1.06 Inches
	Weight	4.76oz
	FCC ID	See website for full list
	Canada Industry ID	See website for full list







Your Local Dealer

Hytera reserves the right to change product designs or specifications at any time. If you have any questions regarding the accuracy of this information please contact your local sales representative or Hytera directly.

איד. Hytera are registered trademarks of Hytera Co., Ltd. © 2014 Hytera Co., Ltd. All rights reserved.





Hytera Communications (Canada) Inc.

Address: 100 Leek Crescent, Unit 11 Richmond Hill, Ontario L4B 3E6 **Tel:** (905) 305-7545 http://www.hytera.ca



Hytera Communications America (West) Inc.

Address: 8 Whatney, Suite 200, Irvine, CA 92618 **Tel:** (949) 326-5740 http://www.hytera.us